

Sentry Power Cords and Cables

Standard Socket Power Cords



| Plug | Plug Image | Outlet | Outlet Image | Part # | Cable Length | Description |
|-------------|---|--------|---|-----------|--------------|--|
| BS 1363 |  | C19 |  | PTCORD-4 | 10ft (3.0m) | BS 1363 (United Kingdom) to IEC 60320 C19, 13A Fuse, 220-240V |
| CEE 7/7 |  | C19 |  | PTCORD-2 | 10ft (3.0m) | CEE 7/7 Schuko to IEC 60320 C19, 16A, 220-240V |
| IEC 60309 |  | C19 |  | PTCORD-3 | 10ft (3.0m) | IEC 60309 16A (Blue/250V, 2P+E, 6hr ground, IP44) to IEC 60320 C19 |
| NEMA 5-15P |  | C19 |  | PTCORD-5 | 10ft (3.0m) | NEMA 5-15P to IEC 60320 C19, 15A, 125V |
| NEMA 5-20P |  | C19 |  | PTCORD-6 | 10ft (3.0m) | NEMA 5-20P to IEC 60320 C19, 20A, 125V |
| NEMA L5-20P |  | C19 |  | PTCORD-7 | 10ft (3.0m) | NEMA L5-20P (Twist Lock) to IEC 60320 C19, 20A, 125V |
| NEMA L6-20P |  | C19 |  | PTCORD-1 | 10ft (3.0m) | NEMA L6-20P (Twist Lock) to IEC 60320 C19, 20A, 208V |
| C14 |  | C13 |  | CAB-1302C | 18in (0.46m) | IEC 60320 C14 to C13, 10A, 125-250V |
| C14 |  | C13 |  | CAB-1302A | 3ft (0.91m) | IEC 60320 C14 to C13, 10A, 125-250V |
| C14 |  | C13 |  | CAB-1302 | 6ft (1.8m) | IEC 60320 C14 to C13, 10A, 125-250V |
| C14 |  | C13 |  | CAB-1302B | 12ft (3.7m) | IEC 60320 C14 to C13, 10A, 125-250V |

Standard Socket Power Cords (cont...)



| Plug | Plug Image | Outlet | Outlet Image | Part # | Cable Length | Description |
|------------|---|------------|---|--------------|--------------|--|
| C14 |  | C13 |  | PTCORDPK-1 | 6ft (1.8m) | 8-pack of CAB-1302 (IEC 60320 C14 to C13, 10A, 125-250V) |
| C14 |  | C13 |  | PTCORDPK-2 | 6ft (1.8m) | 16-pack of CAB-1302 (IEC 60320 C14 to C13, 10A, 125-250V) |
| C14 |  | C19 |  | CAB-1317A | 18in (0.46m) | IEC 60320 C14 to C19, 15A, 125-250V |
| C14 |  | C19 |  | CAB-1317B | 3ft (0.91m) | IEC 60320 C14 to C19, 15A, 125-250V |
| C14 |  | C19 |  | CAB-1317C | 6ft (1.8 m) | IEC 60320 C14 to C19, 15A, 125-250V |
| C14 |  | C19 |  | CAB-1317D | 10ft (3.0m) | IEC 60320 C14 to C19, 15A, 125-250V |
| C14 |  | C15 |  | CAB-C14-C15* | 6ft (1.8m) | IEC 60320 C14 to C15, 15A, 125-250V |
| C14 |  | NEMA 5-15R |  | CAB-1305 | 1ft (0.31m) | IEC 60320 C14 to NEMA 5-15R, 10A, 125V |
| C20 |  | C13 |  | CAB-1350 | 12ft (3.7m) | IEC 60320 C20 to C13, 15A, 125-250V |
| C20 |  | C19 |  | CAB-1311B* | 3ft (0.91m) | IEC 60320 C20 to C19, 20A, 125-250V |
| C20 |  | C19 |  | PMC1-0-1 | 8ft (2.4m) | IEC 60320 C20 to C19, 20A, 125-250V |
| C20 |  | C19 |  | CAB-1311C | 12ft (3.7m) | IEC 60320 C20 to C19, 20A, 125-250V |
| NEMA 5-15P |  | C13 |  | CAB-1301D | 18in (0.46m) | NEMA 5-15P to IEC 60320 C13, 10A, 125-250V |



Standard Socket Power Cords (cont...)



| Plug | Plug Image | Outlet | Outlet Image | Part # | Cable Length | Description |
|------------|---|--------|---|-----------|--------------|--|
| NEMA 5-15P |  | C13 |  | CAB-1301C | 3ft (0.91m) | NEMA 5-15P to IEC 60320 C13, 10A, 125-250V |



| | | | | | | |
|------------|---|-----|---|-----------|------------|--|
| NEMA 5-15P |  | C13 |  | CAB-1301A | 6ft (1.8m) | NEMA 5-15P to IEC 60320 C13, 10A, 125-250V |
|------------|---|-----|---|-----------|------------|--|



Special Order Power Cords — Limited Quantities Available



| | | | | | | |
|---------|---|-----|---|----------|--------------|--|
| AS 3112 |  | C19 |  | CAB-1342 | 8.2ft (2.5m) | Australia/New Zealand AS3112 to IEC 60320 C19, 15A, 250V |
|---------|---|-----|---|----------|--------------|--|



| | | | | | | |
|--------|---|-----|---|------------|--------------|--|
| BS 546 |  | C13 |  | CAB-1380** | 8.2ft (2.5m) | Old British Standard (still used in India and South Africa) BS 546 to IEC 60320 C13, 10A, 250V |
|--------|---|-----|---|------------|--------------|--|



| | | | | | | |
|--------|--|-----|--|----------|--------------|--|
| BS 546 |  | C19 |  | CAB-1345 | 8.2ft (2.5m) | Old British Standard (still used in India and South Africa) BS 546 to IEC 60320 C13, 16A, 250V |
|--------|--|-----|--|----------|--------------|--|



| | | | | | | |
|---------|---|-----|---|----------|------------|--|
| CEE 7/7 |  | C13 |  | CAB-1318 | 8ft (2.4m) | CEE 7/7 Schuko to IEC 60320 C13, 10A, 220-240V |
|---------|---|-----|---|----------|------------|--|



| | | | | | | |
|-----------|---|-----|---|----------|--------------|---|
| CEI 23-16 |  | C19 |  | CAB-1361 | 8.2ft (2.5m) | Italy CEI 23-16 to IEC 60320 C19, 16A, 250V |
|-----------|---|-----|---|----------|--------------|---|

| | | | | | | |
|---------|---|-----|---|----------|--------------|--|
| GB 2099 |  | C19 |  | CAB-1362 | 8.2ft (2.5m) | China GB2099 to IEC 60320 C19, 16A, 250V |
|---------|---|-----|---|----------|--------------|--|

| | | | | | | |
|-----------|---|-----|---|----------|--------------|---|
| IRAM 2073 |  | C19 |  | CAB-1364 | 8.2ft (2.5m) | Argentina IRAM 2073 to IEC 60320 C19, 10A, 250V |
|-----------|---|-----|---|----------|--------------|---|

| | | | | | | |
|----------|---|-----|---|----------|---------------|--|
| JIS 8303 |  | C19 |  | CAB-1365 | 6.56ft (2.0m) | Japan JIS 8303 to IEC 60320 C19, 15A, 125V |
|----------|---|-----|---|----------|---------------|--|

| | | | | | | |
|----------|---|-----|---|----------|--------------|---|
| SEV 1011 |  | C19 |  | CAB-1366 | 8.2ft (2.5m) | Switzerland SEV1011 to IEC 60320 C19, 16A, 250V |
|----------|---|-----|---|----------|--------------|---|

| | | | | | | |
|------|---|-----|---|----------|---------------|---|
| SI32 |  | C19 |  | CAB-1363 | 8.2ft (2.5 m) | Israel SI32 to IEC 60320 C19, 16A, 250V |
|------|---|-----|---|----------|---------------|---|

Special Order Power Cords — Limited Quantities Available (Cont...)

| Plug | Plug Image | Outlet | Outlet Image | Part # | Cable Length | Description |
|------------|---|------------|---|----------------|--------------|--|
| NEMA 6-20P |  | C19 |  | CAB-1354 | 8ft (2.4m) | NEMA 6-20P to IEC 60320 C19, 20A, 208V |
| C14 |  | C13 |  | CAB-1358** | 6.56ft (2m) | IEC 60320 C14 to C13 (Right Angle), 10A |
| (1) C14 |  | (2) C13 |  | CAB-1303 | 6ft (1.8m) | "Y" Cord, IEC 60320 C14 to Dual C13, 10A, 125-250V, 6ft (C14 to "Y" = 4ft, "Y" to each C13 = 2ft) |
| (1) C14 |  | (2) C13 |  | CAB-1303-120** | 10ft (3.0m) | "Y" Cord, IEC 60320 C14 to Dual C13, 10A, 125-250V, 6ft (C14 to "Y" = 4ft, "Y" to each C13 = 10ft) |
| C20 |  | C15 |  | CAB-1343 | 8ft (2.4m) | IEC 60320 C20 to C15, 15A, 125-250V, 8ft Note: C15 fits both C14 and C16 inlets |
| (1) C20 |  | (2) C13 |  | CAB-1353 | 11ft (3.4m) | "Y" Cord, IEC 60320 C20 to Dual-C13, 15A, 125-250V, 11ft (C20 to "Y" = 10 ft, "Y" to each C13 = 1ft) |
| C20 |  | NEMA 5-15R |  | CAB-1314 | 6ft (1.8m) | IEC 60320 C20 to NEMA 5-15R, 15A, 125V |
| NEMA 5-15P |  | C19 |  | CAB-1313 | 8ft (2.4m) | NEMA 5-15P to IEC 60320 C19, 15A, 125V |
| Blunt Cut | — | C19 |  | CAB-1339 | — | IEC 60320 C19 molded to 3-wire bare, 20ft (can be used to create custom length cord using a mechanically-attached plug body). Consult factory before ordering. |

*Please consult STI for pricing and availability as these power cords may need to be special ordered. **Special Order only.

NOTE: Special order cords may require pre-payment. Product samples may not be available. Special order cables may be subject to different restocking restrictions. Specifications and appearance of products may vary and are subject to change without notice.

HEADQUARTERS - NORTH AMERICA

Server Technology, Inc.
 1040 Sandhill Drive
 Reno, NV 89521
 United States
 +00 (1) 775 284 2000 Tel
 +00 (1) 775 284 2065 Fax
 sales@servertech.com
 www.servertech.com
 www.servertechblog.com

EMEA

Server Technology Intl.
 Sienna Court
 The Broadway
 Maidenhead
 Berkshire
 SL6 1NJ
 United Kingdom
 +44 (0) 1628 509053 Tel
 +44 (0) 1628 509100 Fax
 salesintl@servertech.com

APAC

Server Technology, Inc.
 37th Floor, Singapore Land Tower
 50 Raffles Place
 Singapore 048623
 +65 (0) 6829 7008 Tel
 +65 (0) 6234 4574 Fax
 salesintl@servertech.com