

EXPERIENCE SUPERIOR POWER PROTECTION

Integrity 3-Phase Power Conditioners incorporate a low impedance transformer, as well as a surge diverter and a power line filter to eliminate noise, spikes, and transients from effecting the operation for your electronic systems.

Designed for WORLDWIDE applications.

SUITABLE FOR USE WITH:

- > Semiconductor Manufacturing
- Digital Priniting
- Computer Controlled Equipment
-) Lab Automation Systems

SUPERIOR POWER PROTECTION BENEFITS & FEATURES

- Protect your electronic systems and ensure uptime all day, every day.
- Peace of mind knowing equipment is protected from problems due to common-mode voltage, spikes, transients, and more.
- Includes emergency machine off (EMO) and lockout/tagout breaker.

- Let through voltage is less than 10 volts normal mode and less than 0.5 volts. Neutral-to-ground when tested to ANSI/IEEE C62.41, Category A&B.
- Power options from 10 kVA to 150 kVA 3-Phase.
- Provides clean power at 400 delta input and 400/230 wye output.
- CE Marked
- Includes NXT Power 5 Year Warranty





INTERNATIONAL

| MODEL # | INPUT VOLTAGE AC [~] | OUTPUT VOLTAGE AC~ | MAXIMUM POWER (KVA) | FREQUENCY (HZ) |
|--------------|----------------------------------|-----------------------|------------------------|-------------------|
| NPT10.0-H-i | 400 | 400/230 | 10 kVA | 50/60 |
| NPT15.0-H-i | 400 | 400/230 | 15 kVA | 50/60 |
| NPT20.0-H-i | 400 | 400/230 | 20 kVA | 50/60 |
| NPT30.0-H-i | 400 | 400/230 | 30 kVA | 50/60 |
| NPT36.0-H-i | 400 | 400/230 | 36 kVA | 50/60 |
| NPT40.0-H-i | 400 | 400/230 | 40 kVA | 50/60 |
| NPT45.0-H-i | 400 | 400/230 | 45 kVA | 50/60 |
| NPT55.0-H-i | 400 | 400/230 | 55 kVA | 50/60 |
| NPT65.0-H-i | 400 | 400/230 | 65 kVA | 50/60 |
| NPT75.0-H-i | 400 | 400/230 | 75 kVA | 50/60 |
| NPT85.0-H-i | 400 | 400/230 | 85 kVA | 50/60 |
| NPT100.0-H-i | 400 | 400/230 | 100 kVA | 50/60 |
| NPT125.0-H-i | 400 | 400/230 | 125 kVA | 50/60 |
| NPT150.0-H-i | 400 | 400/230 | 150 kVA | 50/60 |

ADDITIONAL PRODUCT INFORMATION

- Measurements of model(s) NPT10.0-H-i to NPT30.0-H-i are 74.4cm(H) x 50.8cm(L) x 83cm(D)
- Measurements of model(s) NPT36.0-H-i to NPT75.0-H-i are 115cm(H) x 50.8cm(L) x 105.2cm(D)
- Measurements of model(s) NPT85.0-H-i to NPT150.0-H-i are 154cm(H) x 71.1cm(L) x 117.1cm(D)

