

# INTEGRITY MAX RT Battery Cabinet

## Product Specifications

MODEL		NPB12-36R
TYPEFORM		Extended Runtime Battery Cabinet
<b>BATTERY</b>	Voltage (VDC)	36
	Battery	12V, High Rate, Valve Regulated Sealed Lead-Acid, Flame Retardant
	Quantity	12
	Charge Current (ADC)	1.8 Amps
	Backup Time (min)	See Run-time Chart
<b>ENVIRONMENTAL</b>	Temperature (°C)	Operating: 0 to 40 °C; Storage: -15 to 55 °C; Transit: -15 to 60 °C
	Altitude (m)	Operating: 2,000; Transit 12,000
	Humidity	5.0% to 95.0%, Non-Condensing
	Heat Dissipation (BTU/hr)	300
<b>AGENCIES</b>	Safety	UI1778 5 <sup>TH</sup> Edition cUL to CSA22.2
	RoHS	All Units are RoHS Compliant (where applicable)
<b>OTHER</b>	Unit Weight (lbs/kg)	82 / 37
	Shipping Weight (lbs/kg)	95 / 43

### Warranty/Support

**NXT Power** warrants the components (including internal batteries) used in its uninterruptible power supplies to be free from defects in materials and workmanship for a period of three years from the date of shipment. See Warranty Statement for complete details. For North American service or support on any NXT Power product, please contact NXT Power at (877) NXT POWR (877-698-7697). In Illinois, call (872) 310-4056. To view the NXT Power Warranty Policy and Procedures, visit [www.nxtpower.com](http://www.nxtpower.com)

### Battery Backup Run Time Chart (UPS Internal Batteries + External Cabinets)

MODEL	# of Cabinets	Load =	25%	50%	75%	100%
NPTU800	1	Run Time =	225	100	75	35
	2	Run Time =	405	180	135	63
NPTU1100	1	Run Time =	150	65	35	20
	2	Run Time =	270	117	63	36
NPTU1440	1	Run Time =	110	40	20	15
	2	Run Time =	198	72	36	27

Notes: Run-Times are in minutes and based on new fully charged batteries at 25 deg C ambient.

### Product Dimensions (Inches)

